



Pressing Unit ACO103

Compact and highperformance efficiency

NEW with rotatable head



- Powerful Milwaukee® Lithium-Ion 180® batteries for reliable performance
- Redundant switch-off and press force control with LED indication
- Automatic pressing cycle
- Safe handling with slipproof rubberized housing and ergonomic design
- Illumination of the press area for safe working
- Analysis of the pressing tool performance via NovoCheck app



Press jaw PB1



Pressing Unit ACO103

Compact and high-performance efficiency

The pressing unit ACO103 has many valuable features to make working easier, faster and safer. The LED signal located under the transparent start button gives information about the battery and the status of the pressing unit or occurred failures. Thanks to the implemented Bluetooth®-Technology, device-related data can be requested via the NovoCheck app.

NovoCheck-App

- Data transfer between pressing tool and app
- Possibility to check the pressing tool's current status
- Analysis of the pressing tool performance
- Integrated report function for documentation of the installation




Scope of application

- Drinking water-, gas- and heating installations, industry and commercial applications and many more
- Suitable for all authorized jaws of other system manufacturers in the market¹
- All common profiles for metal and plastic systems available

Accessories

- Press jaws PB1
- Charger available in many worldwide power supply specifications
- Batteries with different capacities available





Novopress quality and service

Tool features

- Battery-empty-detection
- Error display
- Device information through the LED indication under the start button
- Automatic pressing cycle
- Electronic bolt retention

Maintenance and service

- Qualified service on site thanks to international service network
- Mobile on-site service thanks to our service vehicle in Germany and parts of Europe
- Extended warranty (further information at www.novopress.de)



Technical Data ACO103	
Dimensions ² :	Metal pipe up to 35 mm / Plastic pipe up to 40 mm
Weight without battery:	1.6 kg
Length:	320 mm
Width:	98 mm
Height:	72 mm
Power consumption:	240 W
Piston force:	19 kN
Piston stroke:	30 mm
Battery:	Milwaukee® M12™ battery system³
Battery capacity4:	up to 250 pressing cycles
Charging time ⁵ :	45 - 75 Min.

- 1 for binding information please request your system manufacturer
- 2 system-dependant
- all Milwaukee® capacities in the market can be used
 depending on material, dimension and battery capacity
- 5 depending on battery capacity

We reserve the right to make technical modifications.

